

**WOOD  
INTERIOR**

**PRODUCT DATA SHEET**

# AALTO WOODY'S SECRET

Guarantee is applicable on the use of a full Aalto system

---

**TYPICAL APPLICATION:** A natural oil finish for interior woodwork. Contains tung oil, linseed, polyurethane, beeswax and camphor oil – to give a natural finish emphasising the intrinsic beauty of timber.

---

**PRODUCT FEATURES:**

- + Easy to apply
- + Water resistant
- + Low toxicity
- + Repairable

---

**COLOUR:** Clear amber liquid

---

**PRODUCT DESCRIPTION:**

Appearance when dry:	Flat finish
Pack size:	1, 4 litre
Theoretical coverage:	10-15m <sup>2</sup> /L.
Storage temperature:	Minimum 5°C Maximum 50°C
Film thickness:	Penetrates the timber

---

**APPLICATION:**

**Mixing:** Leave Woody's Secret upside down for approximately 1 hour before use so that the linseed oil, that sinks to the bottom tin, can incorporate itself with the rest of the product. Shake contents thoroughly before use. Stir occasionally during use.

**Initial surface preparation:** Only suitable for application on bare timber. The surface must be clean, dry and free of all dust, dirt, grease, wax and any other surface contaminants. Materials which are loose must be removed and feathered back to a sound surface. Existing surfaces should be washed down with a mild detergent solution and rinsed off with clean water. Any mould should be treated with a proprietary mould kill solution until completely removed and sterilised, then wash to remove all traces of chemical. Patch nail holes with suitable wood filler, allow to dry and sand smooth. Sand timber smooth to desired finish and remove all sharp edges.

**Application note:** Always work in the direction of the grain. Apply in even coats, avoiding overlaps or working back on dry areas. During the month long curing process the wood will develop its full patina.

**Method:** Apply by brush or cloth, allow the timber to absorb Woody's Secret then wipe off excess with a soft cotton cloth. For a fine finish sand lightly with a very fine sand paper between coats, removing all dust prior to the next coat. Apply 2-3 coats of Woody's Secret. Always unfold cloth used to apply Woody's Secret and allow to dry in fresh air, preferably outside, before disposal to avoid spontaneous combustion.

**Note:** If applying to the inside of exterior doors and windows please ensure exterior timber is adequately sealed. This prevents leaching of water inside which can cause staining or damage to the timber and finish.

**Repairing:** To repair the surface at any time, sand out the spot of defect and reapply to that area.

---

**APPLICATION DETAILS:**

Application temperature range:	10°C - 35°C
Methods:	Brush, rag – Always unfold cloth used to apply Woody's Secret and allow to dry outside before disposal to avoid spontaneous combustion.
Thinners:	Mineral turpentine
Max volume thinners:	Do not thin
Cleaning solvent:	Mineral turpentine
Minimum steel temperature:	N/A
Maximum relative humidity:	75%

---

**DRYING CHARACTERISTICS:**

Temperature:	20°C
Touch dry:	4 hours
Handle dry:	12 hours
Full cure:	30 days
	Note: During this month everyday usage is acceptable provided any water spillage is wiped off immediately.
Over-coating:	It is recommended to leave overnight dry between coats. If temperatures are above 20°C over coating can be undertaken after a minimum of 12 hours.

---

**SAFETY:**

Paint class:	3B
Hazchem:	3Y
UN no:	1263

---

**HEALTH AND SAFETY:****CAUTION! FLAMMABLE**

**Keep away from heat. Always unfold cloths used to apply Woody's Secret after use and allow to dry outside to avoid spontaneous combustion.**

Special precautions:	<ul style="list-style-type: none"> <li>+ Keep out of reach of children.</li> <li>+ This material is not to be taken internally.</li> <li>+ Avoid contact with eyes and prolonged contact with skin.</li> <li>+ Avoid breathing vapour - use with adequate ventilation.</li> <li>+ Ensure fresh air is available during application and drying.</li> <li>+ Do not eat, drink or smoke whilst using.</li> <li>+ Store in a cool well ventilated area indoors between 5°C - 20°C</li> <li>+ Seal container after use.</li> <li>+ Protect from freezing</li> <li>+ Dispose of empty container carefully.</li> <li>+ Do not dispose or paint in sewers or waterways.</li> </ul>
Fire:	+ Use foam, carbon dioxide or dry chemical powder.
Spills:	+ Absorb with sand or earth. Collect and seal in properly labelled drums for disposal according to local waste management authority.
FIRST AID: If swallowed:	Give water to dilute. Do not induce vomiting. Get medical advice.
Eye contact:	Flush with running water immediately for at least 15 minutes. Get medical attention.
Inhalation	Leave hazard area, maintain breathing and get medical attention. Remove with soap and water.

---

This information is intended to give a fair description of the product and its capabilities under specific conditions and is correct at the time of printing. It does not constitute an offer by the manufacturers nor do they warrant or guarantee its accuracy of completeness in describing the performance or suitability of the product. The manufacturer's guarantee is only applicable to full Aalto systems and is limited to product replacement only and does not include surface preparation or application. June 2004